



SAFETY DATA SHEET

According to
HSNO Hazardous Substances (Safety Data Sheets) Notice 2017

Section 1. Identification of the material and the supplier

Product: **NPD 100 PLUS**
Product Use: Fuel
Restriction of Use: Refer to Section 15

New Zealand Supplier: **Nelson Petroleum Distributors LTD**
Address: 13 McPherson Street
Richmond
Nelson 7050

Telephone: (+64) 3544 6163
Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 24 August 2020

Section 2. Hazards Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval No: HSR101436

Pictograms



Flammable Chronic Ecotoxic

Signal Word: **DANGER**

NZ HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1A	H224	Extremely flammable liquid and vapour.	Flam. Liq. 1
6.1E (oral)	H303	May be harmful if swallowed.	Acute Tox. 5
6.1E (aspiration)	H304	May be fatal if swallowed and enters airways.	Asp. Tox. 1
6.3B	H316	Causes mild skin irritation.	Skin Irrit. 3
6.7B	H351	Suspected of causing cancer	Carc. 2
6.9B (Repeated exposure)	H373	May cause damage to organs through prolonged or repeated exposure	STOT RE 2
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2
9.3C	H433	Harmful to terrestrial vertebrates.	

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe fumes or vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use CO ₂ , dry powder or foam for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Petrol	< 98%	86290-81-5
N-methyl aniline	2-3%	100-61-8
Additives	< 0.1%	--

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
If on Skin	Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention.
If Swallowed	Do not induce vomiting. Wash out mouth thoroughly with water. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower

than the hips to prevent vomit entering the lungs. Seek immediate medical attention.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion: May be fatal if swallowed and enters airways. May cause pulmonary oedema and chemical pneumonitis. May be harmful if swallowed. Abdominal pain, nausea, blue lips/fingernails.

Inhalation: May cause respiratory irritation, May cause drowsiness, dizziness, headaches and other anaesthetic effects.

Skin: Causes mild skin irritation. Redness, itchiness.

Eye: May cause eye irritation. Redness, itchiness, lacrimation.

Section 5. Fire Fighting Measures

Hazard Type	Extremely Flammable fuel. Vapours may travel considerable distances to a source of ignition. Closed containers may explode when exposed to extreme heat – remove only if safe to do so.
Hazards from combustion products	Oxides of carbon, possible irritating or toxic fumes.
Suitable Extinguishing media	Use CO2 for small fires, dry powder and foam for others.
Precautions for firefighters and special protective clothing	Use equipment suitable for petrol fires (self-contained breathing apparatus and protective equipment).
HAZCHEM CODE	3YE

Section 6. Accidental Release Measures

Wear protective gear as detailed in Section 8 - approved respiratory protection, chemical resistant gloves, protective clothing and safety boots.

Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking. Do not allow to enter drains and water courses.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material. Collect the spilled material and place into a suitable container for disposal. Use only non-sparking tools.

Section 7. Handling and Storage

Precautions for Handling:

- Keep out of reach of children.
- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- For use as a motor fuel only. Do not use as a cleaning solvent. Do not siphon by mouth.
- Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use personal protective equipment as required.

- Use only outdoors or in a well-ventilated area.
- Take precautionary measures against static discharge. This product is a static accumulator.
- Food, beverages and tobacco products should not be stored or consumed where this material is in use.
- Always wash hands before smoking, eating, drinking or using the toilet.
- Wash contaminated clothing and other protective equipment before storage or re-use.
- Provide eyewash fountains and safety showers in close proximity to points of potential exposure.
- Keep container tightly closed.
- Avoid release to the environment.

Precautions for Storage:

- Store locked up.
- Store in a cool, dry and well ventilated area.
- Keep container tightly closed when not in use. Only use approved containers.
- Protect from heat, sparks, open flames and other sources of ignition.
- Store away from incompatible materials listed in Section 10.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³
Petrol	300	890	500	1480
N-methyl aniline	0.5	2.2	-	-

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2019 11TH EDITION.

Engineering Controls

Maintain air concentration below occupational exposure standards, providing adequate ventilation. Use explosion-proof ventilating equipment.

Personal Protection Equipment



Eyes	Eye and face protectors for protection against splashing materials or liquids. See AS/NZS 1337 for more information.
Hands	Chemical resistant nitrile or viton gloves are recommended. See AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.
Skin	Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See AS/NZS 4501 for more information.
Respiratory	Use an approved organic vapour respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapour, inadequate ventilation, development of respiratory tract irritation) and engineering controls are not feasible. See AS/NZS 1715 and 1716 for more information.

General	Maintain basic hygiene standards for normal use.
----------------	--

Section 9 Physical and Chemical Properties

Appearance	Liquid
Colour	Purple
Odour	Petroleum
Odour Threshold	Not available
pH	Not applicable
Boiling Point	> 20°C
Melting Point	Not available
Freezing Point	Not available
Flash Point	-40°C (ASTM D-56)
Flammability	Extremely flammable
Upper and Lower Explosive Limits	Upper: 8.2 Vol % Lower: 1.2 Vol %
Vapour Pressure	69 kPa (at 34°C)
Vapour Density	Not available
Specific Gravity	0.72 - 0.78 (at 15°C)
Water Solubility	Immiscible
Partition Coefficient:	>3 log POW
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Kinematic Viscosity	<1 cSt (at 40°C)

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerisation will not occur.
Conditions to Avoid	Heat, sparks, open flames and other sources of ignition.
Incompatible Materials	Strong oxidising agents, strong acids, bases and halogens.
Hazardous Decomposition Products	Oxides of carbon and sulphur, aldehydes, incomplete combustion products and smoke.

Section 11 Toxicological Information

Acute Effects:

Swallowed	May be harmful if swallowed.
Dermal	Not applicable.
Inhalation	Not applicable. May cause drowsiness, dizziness, headaches and other anaesthetic effects.
Eye	May cause eye irritation.
Skin	Causes mild skin irritation.

Chronic Effects:

Carcinogenicity	Suspected of causing cancer.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Aspiration	May be fatal if swallowed and enters airways.
STOT/SE	Not applicable.
STOT/RE	Prolonged or repeated exposure may cause potentially irreversible damage to the nervous system, kidneys and liver. May cause skin dryness and defatting leading to dermatitis.

Individual component information:**Acute Toxicity:**

Chemical Name	Oral – LD50	Dermal – LD50	Inhalation – LC50
Petrol	>5000 mg/kg (rat)	>2000mg/kg (rabbit)	>5000mg/m ³ (rat)
N-methyl aniline	50-300 mg/kg (rat)	-	-

Section 12. Ecotoxicological Information

HSNO Classes: 9.1B Toxic to aquatic life with long lasting effects.
9.3C Harmful to terrestrial vertebrates.

Product:	
Persistence and degradability	Expected to be inherently biodegradable.
Bioaccumulation	Bioaccumulation is not expected to occur.
Mobility in Soil	Expected to be mobile.
Other adverse effects	No data available

Individual component information (Please refer to www.epa.govt.co.nz for full details):**Petrol (CAS 86290-81-5)**

Route	Species	Duration	Value LC50/EC50
Acute aquatic, fish	Fish	96 hr	100 mg/L
Acute aquatic, Crustacean	Daphnia	48 hr	100 mg/L
Acute aquatic, Algal	Chlorella protothecoides (Green algae)	72hr (static)	>1000 mg/L
Bioaccumulative	Not expected to occur		
Rapidly Degradable	No		

N-methyl aniline (CAS 100-61-8):

No data available – Please refer to www.epa.govt.co.nz for full details

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method: Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled “Hazardous Waste – Flammable, Chronic, Ecotoxic” and that the label also has the Flammable, Chronic, and Ecotoxic Pictograms, waste type identifier, and the business name, address, and phone number.

Precautions or methods to avoid: Avoid release to the environment.

Section 14 Transport Information

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012

**Road, Rail, Sea and Air Transport**

UN No	1203
Class - Primary	3
Packing Group	II
Proper Shipping Name	MOTOR SPIRIT or GASOLINE or PETROL
Marine Pollutant	Yes
Special Provisions	If the product's individual container is below 1L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

Section 15	Regulatory Information
-------------------	-------------------------------

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: HSR101436

HSNO Classification: 3.1A, 6.1E (oral), 6.1E (asp), 6.3B, 6.7B, 6.9B, 9.1B, 9.3C

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity																		
Certified Handler	Not required																		
Location Certificate	50L (3.1A)																		
Signage Trigger Quantities (Schedule 3)	50L (3.1A)																		
Fire Extinguishers (Schedule 4)	50L – 1x extinguisher 200L – 2x extinguishers																		
Emergency Response Plan (Schedule 5)	100L (3.1A)																		
Secondary Containment (Schedule 5)	100L (3.1A)																		
Tracking (Schedule 26)	Not required																		
Restriction of Use	Only use as a fuel.																		
HSNO Additional Controls (Restrictions of use)																			
S 77 – Restriction to Workplaces	NPD 100 PLUS is excluded from Clause 13 of the HPC Notice and the prescribed control is removed.																		
S 77 – Management of large quantities	Clause 19 of the HPC notice applies as if the substance were listed in Schedule 3 of the HPC notice and exceeds 50 L as the specified quantity.																		
S 77A - Restriction on petrol impurities	The following limitations apply to the composition of the component petrol (unleaded): <ul style="list-style-type: none"> • Aromatic hydrocarbons: maximum 55% (volume) • Benzene: maximum 1% (volume) • Additives: (each < 0.1% w/w) <ul style="list-style-type: none"> ○ azo dyes ○ antioxidants ○ metal deactivator ○ corrosion inhibitor • Detergent additives: (each < 0.5% w/w) 																		
Hazardous Property Controls Notice 2017																			
Tolerable Exposure Level (TEL)	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 150px;">Benzene</td> <td>TEL_{air}</td> <td>10 µg/m³</td> </tr> <tr> <td></td> <td>TEL_{water}</td> <td>10 µg/L</td> </tr> <tr> <td>Toluene</td> <td>TEL_{air}</td> <td>400 µg/m³</td> </tr> <tr> <td></td> <td>TEL_{water}</td> <td>800 µg/L</td> </tr> <tr> <td>Xylene</td> <td>TEL_{air}</td> <td>870 µg/m³</td> </tr> <tr> <td></td> <td>TEL_{water}</td> <td>600 µg/L</td> </tr> </table>	Benzene	TEL _{air}	10 µg/m ³		TEL _{water}	10 µg/L	Toluene	TEL _{air}	400 µg/m ³		TEL _{water}	800 µg/L	Xylene	TEL _{air}	870 µg/m ³		TEL _{water}	600 µg/L
Benzene	TEL _{air}	10 µg/m ³																	
	TEL _{water}	10 µg/L																	
Toluene	TEL _{air}	400 µg/m ³																	
	TEL _{water}	800 µg/L																	
Xylene	TEL _{air}	870 µg/m ³																	
	TEL _{water}	600 µg/L																	
Environmental Exposure Level (EEL)	<table style="width: 100%; border-collapse: collapse;"> <tr> <td>EEL_{water} benzene</td> <td>= 2000 µg/L</td> </tr> <tr> <td>EEL_{water} toluene</td> <td>= 330 µg/L</td> </tr> <tr> <td>EEL_{water} o-xylene</td> <td>= 640 µg/L</td> </tr> <tr> <td>EEL_{water} m/p-xylene</td> <td>= 340 µg/L</td> </tr> </table>	EEL _{water} benzene	= 2000 µg/L	EEL _{water} toluene	= 330 µg/L	EEL _{water} o-xylene	= 640 µg/L	EEL _{water} m/p-xylene	= 340 µg/L										
EEL _{water} benzene	= 2000 µg/L																		
EEL _{water} toluene	= 330 µg/L																		
EEL _{water} o-xylene	= 640 µg/L																		
EEL _{water} m/p-xylene	= 340 µg/L																		

Glossary

EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, if further information is required.

Issue Date: 24 August 2020 Review Date: 24 August 2025